

H07 V-R / H05 V-K / (H)07 V-K**

PVC-single cores, fine wire stranded, VDE 0281 approved



Twin tone PVC-Single Cores in Coils

Type	mm – max. ø	Cop. weight kg/km	red-white	blue-white	brown-white	dark blue-white
H05 V-K/mm ²						
part No.			29370	29375	29380	29394
0.5	2.1 - 2.5	4.8				
part No.			29371	29376	29381	29395
0.75	2.2 - 2.7	7.2				
part No.			29372	29377	29382	29396
1	2.4 - 2.8	9.6				
(H)07 V-K**/mm ²						
part No.			29373	29378	29383	29397
1.5	2.8 - 3.4	14.4				
part No.			29374	29379	29384	29398
2.5	3.4 - 4.1	24.0				
part No.			29385	29386	29387	29399
4	3.9 - 4.8	38.0				
part No.			29388	29389	29393	29527
6	4.4 - 5.3	58.0				
part No.			29391	29392	29393	29528
10	5.7 - 6.8	96.0				

Twin tone PVC-Single Cores in Spool

Type	mm – max. ø	Cop. weight kg/km	red-white	blue-white	brown-white	dark blue-white
H05 V-K/mm ²						
part No.			29745	29746	29747	29748
0.5	2.1 - 2.5	4.8				
part No.			29749	29750	29751	29752
0.75	2.2 - 2.7	7.2				
part No.			29753	29754	29755	29756
1	2.4 - 2.8	9.6				
(H)07 V-K**/mm ²						
part No.			29757	29758	29759	29760
1.5	2.8 - 3.4	14.4				
part No.			29761	29762	29763	29764
2.5	3.4 - 4.1	24.0				
part No.			29765	29766	29767	29768
4	3.9 - 4.8	38.0				
part No.			29769	29770	29771	29772
6	4.4 - 5.3	58.0				
part No.			29773	29774	29775	29776
10	5.7 - 6.8	96.0				



Twin tone PVC-Single Cores in Barrels

Type	mm – max. ø	Cop. weight kg/km	red-white	blue-white	brown-white	dark blue-white
H05 V-K/mm ²						
part No.			28948	28949	28950	28951
0.5	2.1 - 2.5	4.8				
part No.			28952	28953	28954	28955
0.75	2.2 - 2.7	7.2				
part No.			28956	28957	28958	28959
1	2.4 - 2.8	9.6				
(H)07 V-K**/mm ²						
part No.			28960	28961	28962	28963
1.5	2.8 - 3.4	14.4				
part No.			28964	28965	28966	28967
2.5	3.4 - 4.1	24.0				
part No.			28968	28969	28970	28971
4	3.9 - 4.8	38.0				
part No.			28972	28973	28974	28975
6	4.4 - 5.3	58.0				
part No.			28976	28977	28978	28979
10	5.7 - 6.8	96.0				

* Please note : The colours yellow, green and transparent are only available in (H)05 V-U resp. (H)07 V-U.

**Two-coloured combination is only permitted for (H)07 V.

U = solid conductor; R = Stranded conductor; K = Fine stranded conductor

Heat resistant versions see types HELUTHERM®. Colours available on request.

PVC cables will be changed to lead free PVC successively.