



Type

Cable

Designation:
Sheath material:
Frequency:

Patch cable S/FTP halogenfree, Cat.6

S/FTP 4x2xAWG 27/7 halogenfree
LSZH
up to 250 MHz

Plug

Push-on connector type 1:
Push-on connector type 2:
Pin assignment:

RJ45 8(8)
RJ45 8(8)
1:1 acc. to TIA/EIA 568 B

Flame proof

acc. to IEC 60332-1-2

Norms and standards

HELUKAT® CONNECTING SYSTEMS® system components up to 250 MHz of category 6 / Class E in accordance with ISO 11801, 2nd edition, EN 50173, 2nd edition, and EIA/TIA 568 B.

Preferred types

Part no.	Sheath colour	Length in metres	Unit
82857	grey	0,5	10
82858	grey	1,0	10
82859	grey	2,0	10
82860	grey	3,0	10
82861	grey	5,0	10
82862	grey	7,5	5
82863	grey	10,0	5
82864	grey	15,0	5

Part no.	Sheath colour	Length in metres	Unit
802999	blue	0,5	10
803000	blue	1,0	10
803001	blue	2,0	10
803002	blue	3,0	10
803003	blue	5,0	10
803004	blue	7,5	5
803005	blue	10,0	5
803006	blue	15,0	5

Part no.	Sheath colour	Length in metres	Unit
803007	green	0,5	10
803008	green	1,0	10
803009	green	2,0	10
803010	green	3,0	10
803011	green	5,0	10
803012	green	7,5	5
803013	green	10,0	5
803014	green	15,0	5

Continuation ►